

Twin-Line Welding Hose Assemblies

Grade R (Acetylene Only)

- Tube: Black EPDM
- Cover: Vulcanized Twin: Green (oxygen), Red (acetylene) EPDM
- Reinforcement: Multiple Textile Spirals
- Temperature range: -20°F to +200°F

WARNING – Grade R is for Acetylene fuel gas only!
Combining the wrong hose and fuel could lead to premature hose failure, property damage and personal injury.

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Wt. (lbs.)
7126NLC-150	Red/Green	3/16	12-1/2	10	2 ea.
7126NLC-300	Red/Green	3/16	25	10	4 ea.
7126NLC-600	Red/Green	3/16	50	5	7 ea.
7126NLF-150	Red/Green	1/4	12-1/2	10	2 ea.
7126NLF-300	Red/Green	1/4	25	10	6 ea.
7126NLF-600	Red/Green	1/4	50	5	11 ea.
7126NLM-300	Red/Green	3/8	25	10	8 ea.
7126NLM-600	Red/Green	3/8	50	5	15 ea.



Grade T (All Fuel Gases)

- Tube: Black Neoprene
- Cover: Green (oxygen), Red (fuel gas) Neoprene
- Reinforcement: Multiple Textile Spirals
- Temperature range: -40°F to +200°F

WARNING – If you are using a fuel gas other than acetylene, you should use Grade T hose! Combining the wrong hose and fuel could lead to premature hose failure, property damage and personal injury.

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Wt. (lbs.)
7109NLC-150	Red/Green	3/16	12-1/2	10	2 ea.
7109NLC-300	Red/Green	3/16	25	10	4 ea.
7109NLC-600	Red/Green	3/16	50	5	7 ea.
7109NLF-150	Red/Green	1/4	12-1/2	10	3 ea.
7109NLF-300	Red/Green	1/4	25	10	6 ea.
7109NLF-600	Red/Green	1/4	50	5	11 ea.
7109NLM-300	Red/Green	3/8	25	10	8 ea.
7109NLM-600	Red/Green	3/8	50	5	16 ea.



This durable two-sided display rack effectively showcases Parker's cut & coupled industrial hose products. It is constructed from metal and stands 60" H x by 20" W x 25" D. Three shelves per side hold ample coiled product, and each shelf has a slide-in channel for a product label or graphic. A plastic frame holds a two-sided header sign. The rack is easy to assemble with a provided wrench and has four floor glides for easy mobility.

Parker
Industrial Hose

Parker Hannifin Corp.
Industrial Hose Division
Strongsville, OH
www.parker.com/indhose
Toll Free IHP Customer Service:
(866) 810-HOSE
(866) 810-4673

© 2007 Parker Hannifin Corporation
Information and specifications subject to change without notice and without liability therefor.

Parker
Industrial Hose

CUT & COUPLED
HOSE ASSEMBLIES

FOR
COMMERCIAL
INDUSTRIAL
CONTRACTORS
FARM / AG



Rubber Air Hose 200 PSI

- Abrasion-resistant EPDM rubber tube & cover
- 2-spiral textile reinforcement
- Working temperature range: -40°F to +212°F
- Strain-relief sleeve, coiled with cardboard discs
- Brass fittings with male 1/4" x 1/4" NPT thread

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Pack Wt. (lbs.)
7092252-KAD	Red	1/4	25	10	26
7092252-KAC	Red	1/4	50	5	26
7092382-KAD	Red	3/8	25	10	38
7092382-KAC	Red	3/8	50	5	38
7093252-KAC	Black	1/4	50	5	25
7093382-KAC	Black	3/8	50	5	37



Heavy-Duty Rubber Air Hose 300 PSI

- Abrasion-resistant EPDM rubber tube & cover
- Heavy-duty reinforcement
- Working temperature range: -40°F to +160°F
- Strain-relief sleeve
- Brass fittings with male 1/4" x 1/4" NPT threads

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Pack Wt. (lbs.)
7092253-KAB	Red	1/4	25	10	30
7092253-KAA	Red	1/4	50	5	30
7092383-KAB	Red	3/8	25	10	43
7092383-KAA	Red	3/8	50	5	42
7093253-KAA	Black	1/4	50	5	30
7093383-KAA	Black	3/8	50	5	42



Hurricane Pressure Washer Hose 3000 PSI

- Tube: Black Neoprene
- Cover: Black (BK) or non-marking blue (BL) Neoprene
- Reinforcement: One wire braid
- Temperature range: -40° F to 250° F

WARNING! Not for steam service. Not intended for carpet cleaning applications.

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Pack Wt. (lbs.)
725825BKRS-600	Black	1/4	50	5	35
725825BLRS-600	Blue	1/4	50	5	35
725838BKRS-600	Black	3/8	50	5	50
725838BLRS-600	Blue	3/8	50	5	50



Contractor's Water Hose - Rubber

- 7093 is 200 PSI, 7055 is 100 PSI
- Weather- and abrasion-resistant EPDM rubber
- Heavy-duty reinforcement
- Working temperature range: -40°F to +180°F
- Strain-relief sleeve
- Heavy-duty machined-brass garden-hose-thread fittings

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Pack Wt. (lbs.)
7093BCWGH-600	Black	3/4	50	3	48
7055GHT63-300	Black	5/8	25	10	44
7055GHT63-600	Black	5/8	50	5	44
7055GHT75-300	Black	3/4	25	6	40
7055GHT75-600	Black	3/4	50	3	40



Heavy-Duty Rubber Jiffy® Push-On Air Hose 300 PSI

- Oil-resistant hose, excellent for use with air tools
- Light, flexible and couples in a Jiffy – no clamps or special tools needed
- Working temperature range: -40°F to +212°F
- Flame-resistant cover

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Pack Wt. (lbs.)
7212BL25-J050	Blue	1/4	50	5	23
7212BL25-J100	Blue	1/4	100	5	45
7212GY25-J050	Gray	1/4	50	5	23
7212GY25-J100	Gray	1/4	100	5	45
7212BL38-J050	Blue	3/8	50	5	30
7212BL38-J100	Blue	3/8	100	3	36
7212GY38-J050	Gray	3/8	50	5	30
7212GY38-J100	Gray	3/8	100	3	36



Jackhammer Hose Standard 200 PSI

- Abrasion-resistant EPDM rubber tube & cover
- Temperature range: -40°F to +212°F
- Available in bulk-packaged quantities
- Premium quality crimped-on universal couplings

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Wt. (lbs.)
7081JHE75-600	Red	3/4	50	1	14 ea.
7081JHE75-600B	Red	3/4	50	36	14 ea.



Sledgehammer Hose Premium 300 PSI

- Abrasion-resistant EPDM rubber tube & cover
- Temperature range: -40°F to +212°F
- Available in bulk-packaged quantities
- Premium quality crimped-on universal couplings

Part Number	Color	I.D. (in.)	Length (ft.)	Std. Pack	Wt. (lbs.)
7082JHP75-600	Red	3/4	50	1	19 ea.
7082JHP75-600B	Red	3/4	50	36	19 ea.
7083JHP75-600	Yellow	3/4	50	1	19 ea.
7083JHP75-600B	Yellow	3/4	50	36	19 ea.